




ZCC Cutting Tools Europe GmbH

Product Innovations

09/2023

[XLR chip breaker – zType threading tool holders with internal cooling –
ONMX high feed turning system – PNMX high feed turning system – FD flat drills]

The Company

Zhuzhou Cemented Carbide Cutting Tools Co., Ltd. (ZCC-CT), based in Zhuzhou, China, is the largest Chinese manufacturer of carbide tools. It is also a key company of China Tungsten High-Tech Material Co. Ltd. part of the China Minmetals Corporation.

Since its founding in 1953, ZCC Cutting Tools Co., Ltd. has grown to become one of the world's leading carbide manufacturers with more than 2,000 employees by using the latest technologies and employing highly skilled personnel. The company continuously modernises production technologies and expands its production capacities to enable the company's ongoing growth. As part of Minmetals Corporation, ZCC-CT is able to cover the entire value chain of modern carbide tool production itself, from raw material extraction through to the coated end product and all associated intermediate steps.

By drawing on the latest in European production technology, the company offers products that consistently meet the highest quality standards. Our extensive product range includes carbide/solid carbide, cermet, CBN, PCD and ceramic inserts, carbide tools, tool holders, milling bodies and the accompanying tool systems. All products are consistently produced to accepted international standards, including ISO, DIN, ANSI, JIS and BSI. In addition, ZCC-CT offers customised solutions and special carbide products built to individual specifications.

ZCC-CT invests heavily in research and development. The associated investments go beyond that of most competitors. ZCC Cutting Tools' excellently trained engineers, scientists and a competent, international team, research the necessary fundamentals. These form the basis for the ongoing development of new products and the improvement of existing ones.

The company continuously introduces improvements in quality to meet the customers' ever-increasing demands for new and innovative products and to maximise the benefit of each individual

customer. Both production and administration in China are subject to the ISO 9001:2008 standard, while environmental management is subject to the requirements set out in ISO 14001:2004.

The foundation of the European headquarters of ZCC-CT, ZCC Cutting Tools Europe GmbH and the European central warehouse, both located in Düsseldorf (Germany), dates back to 2003. Today, all European countries as well as the adjacent markets are served from there.

The quality management system of ZCC Cutting Tools Europe GmbH is certified in the area of 'distribution and logistics of metal-working tools' in accordance with ISO 9001:2008.

The Test and Demonstration Centre is available for optimizing customer processes according to individual requirements.


External sales staff and distribution partners in Europe work hand in hand to support customers across the region. Our friendly ZCC-CT application engineers are also available to support you with their expertise and experience by phone, e-mail or in person at your production facility.

The entire field and office sales force is available to answer enquiries from clients across Europe in their native language. Together with employees from the logistics team and with the help of a sophisticated service system, they ensure that all orders are delivered as quickly as possible to you. Branch offices in France and Great Britain add to additional regional proximity to customers.

ZCC Cutting Tools Europe GmbH and all of our employees are there for you and have your back as a competent partner for all matters concerning machining production. This is how we define 'your partner – your value'.



Member of Minmetals Group



This brochure will be presenting the following new products:

Product Innovations 09 / 2023

GENERAL TURNING

Page



XLR chip breaker – Roughing made easy

A11



ONMX high feed turning system – New Octa insert and tool holder series for efficient turning applications

A16



PNMX high feed turning system – New Penta insert and tool holder series for efficient turning applications

A20

THREADING

Page



zType threading tool holders with internal cooling – New series for high-quality results in threading operations

A28

SOLID CARBIDE DRILLING

Page



FD flat drills – 180° solid carbide drills for any application

C38



A glimpse inside: Highlights from previous Product Innovations brochures

Product Innovations 03 / 2023

GENERAL TURNING

YBG205H grade – The perfect choice for high-temperature turning applications

PARTING & GROOVING

MU chip breaker – Universal tool that delivers optimum chip control

INDEXABLE MILLING

FME17 face milling system – Highly efficient universal tool for machining end faces and contours

EMP05 plunge milling system – Universal tool for any machining application

FMR06 round insert milling cutter – Maximum cutting performance

CSX1000 grade – High-performance grade for superalloys

APL chip breaker – Universal geometry



[Go to PDF online](#)

Product Innovations 09 / 2022

GENERAL TURNING

XMH chip breaker – Semi-finishing made easy

THREADING

zType threading inserts – New series for high-quality results in threading operations

INDEXABLE MILLING

FMA12 face milling system – Now available in new ONHU09T5 insert size

EMP14 aluminium milling system – Precisely 90° for shoulder milling operations

FMR11 round insert milling cutter – Maximum cutting performance

SOLID CARBIDE MILLING

VPM series – Now also available as a torus milling cutter/with Weldon clamping surface



[Go to PDF online](#)

Product Innovations 05 / 2022

GENERAL TURNING

miniTURN – New YPG202 grade for enhanced performance

INDEXABLE MILLING

YBG205H grade – Optimal for high-temperature applications

FMP06 – High-performance hard machining with 88° approach angle

FMA17 – Versatile milling system for efficient facing operations

FMP17 – Efficient universal tool for machining end faces and contours

FMR04 – Extension: Now with new inserts and chip breakers

SOLID CARBIDE MILLING

TM series – Expanded line with compact torus milling cutters from Ø1.0 mm

VPM series – High-speed full-slot milling

SOLID CARBIDE DRILLING

UD series – Extension: Now available in diameters from 1.0 mm with internal cooling



[Go to PDF online](#)

General turning

ISO code – general turning inserts
ISO code – external tool holders
XLR chip breaker
ONMX high feed turning system
PNMX high feed turning system

A6–A7
A8–A9
A10–A15
A16–A19
A20–A24



A
Turning
B
Milling
C
Drilling
D
Technical Information
E
Index

ISO standard

T N M G 22 04 08 (N) – DM

1 2 3 4 5 6 7 8 9

Insert shape		
A	B	C
D	E	H
K	L	M
O	P	R
S	T	V
W	Z Special	

1

Clearance angle	
A	B
C	D
E	F
G	N
P	O Special

2

Tolerance class			
Code	I.C [mm]	m [mm]	S [mm]
A	±0,025	±0,005	±0,025
C	±0,025	±0,013	±0,025
E	±0,025	±0,025	±0,025
F	±0,013	±0,005	±0,025
G	±0,025	±0,025	±0,130
H	±0,013	±0,013	±0,025
J	±0,05–0,15	±0,005	±0,025
K	±0,05–0,15	±0,013	±0,025
L	±0,05–0,15	±0,025	±0,025
M	±0,05–0,15	±0,08–0,20	±0,130
N	±0,05–0,15	±0,08–0,20	±0,025
U	±0,08–0,25	±0,13–0,38	±0,130


3

Fastening features (metric)	
Insert shape	
A	B
C	F
G	H
J	M
N	Q
R	T
U	W
X Special	


4

Cutting edge length l [mm]							
I.C [mm]	Insert shape						
3,97							
5,0							
5,56							
6,0							
6,35	06	07			11	11	
8,0							
9,525	09	11	09	09	16	16	06
10,0							
12,0							
12,7	12	15	12	12	22	22	08
15,875	16		15	15	27		
16,0		19	16				
19,05	19		19	19	33		
20,0							
25,0	25	25	25				
25,4			25	25			
31,75			31				
32			32				


5

Insert thickness S [mm]			
			
Code	S	Code	S
00	0,79	T5	5,95
T0	0,99	06	6,35
01	1,59	T6	6,75
T1	1,98	07	7,94
02	2,38	09	9,52
T2	2,58	T9	9,72
03	3,18	11	11,11
T3	3,97	12	12,70
04	4,76		
T4	4,96		
05	5,56		

6

Nose radius r [mm]	
	
Code	r
00	–
02	0,2
04	0,4
08	0,8
12	1,2
16	1,6
20	2,0
24	2,4
32	3,2
X	Special
MO	Round inserts

7



8

Chip breaker overview
(on page A16 in the Main Catalogue)

9

ANSI standard

T	N	M	G	4	3	2	(N)	–	DM
1	2	3	4	5	6	7	8		9

Inner circle		
Code	[mm]	Pouce
2	6.35	0.250
3	9.525	0.375
4	12.7	0.500
5	15.875	0.625
6	19.05	0.750
8	25.4	1.000

5

Insert thickness		
Code	[mm]	Pouce
2	3.18	0.125
3	4.76	0.187
4	6.35	0.250
5	7.94	0.313
6	9.52	0.375

6

Nose radius		
Code	[mm]	Pouce
0	0.2	0.008
1	0.4	0.016
2	0.8	0.031
3	1.2	0.047
4	1.6	0.063
5	2.0	0.079
6	2.4	0.094

7

A

P C L N L 25 25 M 12

1 2 3 4 5 6 7 8 9

Turning

B

Milling

C

Drilling




D

Technical Information


E

Index

Clamping system			Insert shape	
Code	Description			
P	Lever lock clamping		C	
M	Wedge/pin lock clamping		D	
S	Screw-on clamping		R	
C/J	Wedge clamping		S	
D	Dual wedge clamping		T	
			V	
			W	
1			2	


Tool holder type and entering angle					Clearance angle	
					B	
A	B	C	D	E	C	
					D	
F	G	H	J	K	E	
					N	
L	M	N	O	P	P	
						
Q	R	S	T	U		
						
V	W	X				
3					4	

Cutting direction



5


Shank height h [mm]



Code	h
12	12
16	16
20	20
25	25
32	32
40	40
50	50

6

Shank width b [mm]



Code	b
12	12
16	16
20	20
25	25
32	32
40	40
50	50

7

Holder length L [mm]



Code	L
H	100
K	125
M	150
P	170
Q	180
R	200
S	250
T	300

8

Cutting edge length l [mm]

Insert shape

I.C [mm]	Insert shape						
							
	C	D	R	S	T	V	W
5,56	09						
6,35	06	07	11				
9,525	09	11	09	09	16	16	06
12,7	12	15	12	12	22	22	08
15,875	16	19	15	15	27		
19,05	19	19		19	33		
25,4	25	25		25	44		
32	32						

9

A

Turning

B

Milling

C

Drilling

D

Technical
Information

E

Index

XLR chip breaker

Roughing made easy

YOUR BENEFITS

- Positive geometry **for low cutting forces at high feed rates** and cutting depths
- Recommended for low-power machines
- Excellent chip control even at maximum material removal rates thanks to optimum positioning of chip-forming elements





Fig.: CNMG120408-XLR YBC103

Turning inserts

-  Ideal machining conditions
 Normal machining conditions
 Unfavourable machining conditions

CN**	L	I.C	S	d
12 04	12,9	12,7	4,76	5,16
16 06	16,1	15,875	6,35	6,35
19 06	19,3	19,05	6,35	7,94

CN** negative insert				HC ¹ (CVD)												HC ¹ (PVD)				HT	HC ²	HW							
				P																									
				M																									
				K																									
				N																									
				S																									
				H																									
ISO		r	a _p	f	YBC103	YB6315	YBC152	YBC203	YBC252	YBC352	YBM153	YBM253	YBD102	YB7315	YBD152	YBD152C	YBG101	YBG102	YBG105	YBG205	YB9320	YPD201	YBS103	YNG151	YNT251	YNG151C	YD101	YD201	
XLR  Roughing	CNMG120408-XLR	0.8	1.5-6.0	0.2-0.40	●			●																					
	CNMG120412-XLR	1.2	1.5-6.0	0.2-0.50	●			●																					
	CNMG120416-XLR	1.6	1.5-6.0	0.2-0.55	●			●																					
	CNMG160608-XLR	0.8	1.5-7.0	0.2-0.40	●			●																					
	CNMG160612-XLR	1.2	1.5-7.0	0.2-0.50	●			●																					
	CNMG160616-XLR	1.6	1.5-7.0	0.2-0.55	●			●																					
	CNMG190612-XLR	1.2	2.5-7.8	0.2-0.55	●			●																					
	CNMG190616-XLR	1.6	2.5-7.8	0.2-0.60	●			●					●																
	CNMG190624-XLR	2.4	2.5-7.8	0.20-0.65	○			●																					
XLR  Roughing	CNMM120408-XLR	0.8	1.5-6.0	0.2-0.4	●			●																					
	CNMM120412-XLR	1.2	1.5-6.0	0.2-0.5	●			●					○																
	CNMM120416-XLR	1.6	1.5-6.0	0.2-0.55	●			●																					
	CNMM160608-XLR	0.8	1.5-7.0	0.2-0.4	●			●																					
	CNMM160612-XLR	1.2	1.5-7.0	0.2-0.55	●			●																					
	CNMM160616-XLR	1.6	1.5-7.0	0.2-0.60	●			●																					
	CNMM160624-XLR	2.4	1.5-7.0	0.2-0.65	●																								
	CNMM190612-XLR	1.2	2.0-7.8	0.2-0.55	●			●																					
	CNMM190616-XLR	1.6	2.0-7.8	0.2-0.6	●			●																					
	CNMM190624-XLR	2.4	2.0-7.8	0.2-0.65	●			●																					

● Ex stock ○ On demand

HC¹ Coated carbide
 HT Uncoated cermet
 HC² Coated cermet
 HW Uncoated carbide

A

Turning

B

Milling

C

Drilling

D

Technical Information

E

Index


A

Turning

Turning inserts

- Ideal machining conditions
- Normal machining conditions
- Unfavourable machining conditions

DNMG	L	I.C	S	d
15 06	15,5	12,7	6,35	5,16

DN** negative insert				HC ¹ (CVD)										HC ¹ (PVD)				HT	HC ²	HW								
				P	●	●	●	●	●					●	●	●	●											
				M						●	●			●	●	●	●	●	●									
				K								●	●	●	●													
				N										●	●					●	●							
				S											●	●	●	●	●		●	●						
				H																								
ISO		r	a _p	f	YBC103	YB6315	YBC152	YBC203	YBC252	YBC352	YBM153	YBM253	YBD102	YB7315	YBD152	YBD152C	YBG101	YBG102	YBG105	YBG205	YB9320	YPD201	YBS103	YNG151	YNT251	YNG151C	YD101	YD201
XLR	DNMG150608-XLR	0.8	1.5-4.8	0.2-0.48	●			●																				
	DNMG150612-XLR	1.2	1.5-4.8	0.2-0.45	●			●																				
	DNMG150616-XLR	1.6	1.5-4.8	0.2-0.50	●			●																				
Roughing																												

● Ex stock ○ On demand

HC¹ Coated carbide
HT Uncoated cermet
HC² Coated cermet
HW Uncoated carbide

B

Milling

C

Drilling

D

Technical Information


E

Index

Turning inserts

- Ideal machining conditions
- ⊗ Normal machining conditions
- ⊗ Unfavourable machining conditions

SNMM	L	I.C	S	d
25 09	25,4	25,4	9,525	9,12

SN** negative insert					HC' (CVD)								HC' (PVD)				HT	HC ²	HW										
					P																								
					M																								
					K																								
					N																								
					S																								
					H																								
ISO	r	a _p	f		YBC103	YB6315	YBC152	YBC203	YBC252	YBC352	YBM153	YBM253	YBD102	YB7315	YBD152	YBD152C	YBG101	YBG102	YBG105	YBG205	YB9320	YPD201	YBS103	YNG151	YNT251	YNG151C	YD101	YD201	
XLR	SNMM250924-XLR	2,4	2,0-7,8	0,2-0,65																									
																													
Roughing																													

● Ex stock ○ On demand

HC¹ Coated carbide
HT Uncoated cermet
HC² Coated cermet
HW Uncoated carbide

A

Turning

B

Milling

C

Drilling

D

Technical
Information

E

Index


A

Turning

Turning inserts

- Ideal machining conditions
- ⊗ Normal machining conditions
- ⊗ Unfavourable machining conditions

TNMG	L	I.C	S	d
16 04	16,5	9,525	4,76	3,81

TN** negative insert				HC ¹ (CVD)										HC ¹ (PVD)				HT	HC ²	HW																																																																																																																																																																																																																																																																																																																																																																																																																																																			
				P																																																																																																																																																																																																																																																																																																																																																																																																																																																																			</

● Ex stock ○ On demand

HC¹ Coated carbide
 HT Uncoated cermet
 HC² Coated cermet
 HW Uncoated carbide

B

Milling

C


Drilling

D

Technical Information

E

Index

A close-up photograph of a metal chip breaker installed on a lathe. The chip breaker is a small, white, L-shaped tool mounted on a metal block. It is positioned to break chips from a rotating workpiece, which is visible as a blurred metal cylinder on the left. The background is a blurred industrial setting.


XLR chip breaker

ONMX high-feed turning system

New Octa insert and tool holder series for efficient turning applications

YOUR BENEFITS

- For applications ranging from highly efficient medium machining to roughing
- Extremely efficient, double-sided insert with **sixteen cutting edges**
- High feed leads to **shorter machining times**
- Target cooling for **improved chip removal** and a **long tool life**
- New, optimised **XH chip breaker** for **enhanced chip control**



Insert grades


YBC103

CVD
P05–P15
M10–M20

YBC203

CVD
P15–P25
M15–M25

Application field



Chip breaker


-XH



Finishing to medium
machining

a_p [mm]	f [mm/r]
0,5–1,5	0,4–1,5

Controlled chip removal thanks to
optimised chip-forming elements



Highly economical thanks
to **sixteen cutting edges**

In combination with our **YBC103** and
YBC203 high-performance grades

Fig.: ONMX050512-XH YBC103


A

Turning

Turning inserts

- Ideal machining conditions
- Normal machining conditions
- Unfavourable machining conditions

ONMX	L	I.C	S	d
05 05	5,96	12,7	5,56	4,64

ON** negative insert				HC ¹ (CVD)										HC ¹ (PVD)				HT	HC ²	HW								
				P																								
				M																								
				K																								
				N																								
				S																								
				H																								
ISO		r	a _p	f	YBC103	YB6315	YBC152	YBC203	YBC252	YBC352	YBM153	YBM253	YBD102	YB7315	YBD152	YBD152C	YBG101	YBG102	YBG105	YBG205	YB9320	YPD201	YBS103	YNG151	YNT251	YNG151C	YD101	YD201
XH	ONMX050512-XH	1.2	0.5-1.5	0.4 – 1.5	●			●																				
																												
Finishing																												

● Ex stock ○ On demand

HC¹ Coated carbide
HT Uncoated cermet
HC² Coated cermet
HW Uncoated carbide

B

Milling

C


Drilling

D

Technical Information

E

Index




ON** holder (external) S-Clamping

SOXNR/L Kr: 23°



Right hand style



Article	*	Stock		Dimensions [mm]							Inserts
		R	L	a	b	L	h	s	e	M	
SOXNL2020X05C	*	●		20	20	105	20	21.7	35	G1/8	ONMX0505
SOXNR2020X05C	*	●		20	20	105	20	21.7	35	G1/8	ONMX0505
SOXNL2525X05C	*	●		25	25	120	25	26.7	35	G1/8	ONMX0505
SOXNR2525X05C	*	●		25	25	120	25	26.7	35	G1/8	ONMX0505

● Ex stock ○ On demand

* With internal cooling

Spare parts			
	Insert	ONMX0505	ONMX0505
	h	20	25
	Grub screw	PT1/8×7	PT1/8×7
	Screw	I60M4×15 (3.4 Nm)	I60M4×15 (3.4 Nm)
	Shim	O05BM	O05BM
	Wrench (screw)	WT15IP	WT15IP
	Wrench (shim)	WH50L	WH50L

Insert



Finishing

A

Turning

B

Milling

C

Drilling

D

Technical
Information

E


Index

PNMX high-feed turning system

New Penta insert and tool holder series for efficient turning applications

YOUR BENEFITS

- For applications ranging from highly efficient medium machining to roughing
- Efficient, double-sided insert with **ten cutting edges**
- High feed and removal rates lead to **shorter machining times**
- Target cooling for **improved chip removal** and a **long tool life**
- New, optimised **XH chip breaker** for **enhanced chip control**



Insert grades


YBC103

CVD
P05–P15
M10–M20

YBC203


CVD
P15–P25
M15–M25

Application field



Chip breaker

-XH



Medium machining to
roughing

a_p [mm]	f [mm/r]
1,0–3,0	0,4–1,5

Controlled chip removal thanks to
optimised chip-forming elements

In combination with our **YBC103** and
YBC203 high-performance grades

Highly economical
thanks to **ten cutting edges**




Abb.: PNMx090512-XH YBC103


A

Turning

Turning inserts

- Ideal machining conditions
- Normal machining conditions
- Unfavourable machining conditions

PNMX	L	I.C	S	d
09 05	9.77	12.7	5.56	4.64

PN** negative insert				HC ¹ (CVD)										HC ¹ (PVD)					HT	HC ²	HW						
				P																							
				M																							
				K																							
				N																							
				S																							
				H																							
ISO	r	a _p	f	YBC103	YB6315	YBC152	YBC203	YBC252	YBC352	YBM153	YBM253	YBD102	YB7315	YBD152	YBD152C	YBG101	YBG102	YBG105	YBG205	YB9320	YPD201	YBS103	YNG151	YNT251	YNG151C	YD101	YD201
XH	PNMX090512-XH	1.2	1.0-3.0	0.4 – 1.5	●		●																				
 Medium Cut																											

● Ex stock ○ On demand

HC¹ Coated carbide
 HT Uncoated cermet
 HC² Coated cermet
 HW Uncoated carbide

B

Milling

C


Drilling

D

Technical Information

E

Index




PN** holder (external)

S-Clamping

SPXNR/L Kr: 23°



Right hand style



Article	*	Stock		Dimensions [mm]							Inserts
		R	L	a	b	L	h	s	e	M	
SPXNL2525X09C	*	●		25	25	120	25	28.4	35	G1/8	PNMX0905
SPXNR2525X09C	*	●		25	25	120	25	28.4	35	G1/8	PNMX0905
SPXNL3225X09C	*	●		32	25	135	32	28.4	35	G1/8	PNMX0905
SPXNR3225X09C	*	●		32	25	135	32	28.4	35	G1/8	PNMX0905

● Ex stock ○ On demand

* With internal cooling

Spare parts

	Insert	PNMX0905	PNMX0905
	h	25	32
	Grub screw	PT1/8×7	PT1/8×7
	Screw	I60M4×15 (3.4 Nm)	I60M4×15 (3.4 Nm)
	Shim	P09BM	P09BM
	Wrench (screw)	WT15IP	WT15IP
	Wrench (shim)	WH50L	WH50L

Insert



Medium Cut

A

Turning

B

Milling

C

Drilling

D

Technical
Information

E

Index

A close-up photograph of a high-feed turning operation. A polished, cylindrical metal workpiece is being machined by a lathe. A cutting tool, mounted on a tool holder, is positioned to cut the workpiece. The tool holder is a dark, heavy-duty metal component with two visible screws. The background is blurred, showing the industrial environment of a machine shop.

PNMX high-feed turning system

Threading

System code – threading tool holders	A26
z-Type threading tool holders with internal cooling	A28–A33



A

Turning

B

Milling

C

Drilling

D

Technical
Information

E

Index

Z S E R 20 20 K 16 (C)

1

2

3

4

5

6

7

8

9

Series

Clamping system

Code

Description

S

Screw clamping



C

Top clamping



Application

Code

Description

E

External thread tool holder

I

Internal thread tool holder

1


2

3


Cutting direction



Shank height h [mm]



Shank width b / Shank diameter d [mm]



4

5

6

Shank length L [mm]



Code

L

F

80

H

100

K

125

M

150

P

170

Q

180

R

200

S

250

T

300

7

Insert size [mm]

Code

Height

11

6,35

16

9,525


22

12,7

8

Internal cooling

9



zType threading tool holders


zType threading tool holders with internal cooling

New series for high-quality results in threading operations

YOUR BENEFITS

- Target cooling for **optimum chip removal** and a **long tool life**
- **Higher productivity** thanks to reduced machining temperature
- Wide assortment of zType threading inserts available

ZSER2525R16C external tool holders



Insert grades

YBG205

PVD
P15–P25
M15–M25

Inserts


Z16IR1.5ISOPP



The accompanying **threading inserts** from the new **zType series** can be found in **Product Innovations 09/2022**. Scan the QR code to open and view the brochure.




ZSIR0025M16C boring bar



Threading tool holder (external)

ZSER/L



Article	*	Stock	Dimensions [mm]					Inserts
			a	b	L	h	s	
ZSER1616F16C	*	○	16	16	80	16	20	Z16ER**
ZSER2020H16C	*	○	20	20	100	20	25	Z16ER**
ZSER2525K16C	*	○	25	25	125	25	32	Z16ER**
ZSER3232K16C	*	○	32	32	125	32	32	Z16ER**
ZSER2525K22C	*	○	25	25	125	25	40	Z22ER**
ZSER3232K22C	*	○	32	32	125	32	40	Z22ER**


● Ex stock ○ On demand

* With internal cooling

Spare parts			
	Insert	Z16ER**	Z22ER**
	h	16-32	25-40
	Grub screw	PT1/8×4	PT1/8×4
	Screw		I60M5×17 (6.7 Nm)
	Screw	I60M3.5×12TT (2.7 Nm)	
	Screw (shim)	SM4×8C (2.6 Nm)	SM5×8.5C (4.0 Nm)
	Shim	MT16-__MN	MT22-__MN
	Wrench (screw)	WT15IP	WT20IP

Threading tool holder (external)

ZSER/L



Article	*	Stock	Dimensions [mm]					Inserts
			a	b	L	h	s	
ZSEL1616F16C	*	○	16	16	80	16	20	Z16EL**
ZSEL2020H16C	*	○	20	20	100	20	25	Z16EL**
ZSEL2525K16C	*	○	25	25	125	25	32	Z16EL**
ZSEL3232K16C	*	○	32	32	125	32	32	Z16EL**
ZSEL2525K22C	*	○	25	25	125	25	40	Z22EL**
ZSEL3232K22C	*	○	32	32	125	32	40	Z22EL**

● Ex stock ○ On demand

* With internal cooling

Spare parts			
	Insert h	Z16EL** 16-32	Z22EL** 25-40
	Grub screw	PT1/8×4	PT1/8×4
	Screw		I60M5×17 (6.7 Nm)
	Screw	I60M3.5×12TT (2.7 Nm)	
	Screw (shim)	SM4×8C (2.6 Nm)	SM5×8.5C (4.0 Nm)
	Shim	MT16-__MN	MT22-__MN
	Wrench (screw)	WT15IP	WT20IP

A

Turning

B

Milling

C


Drilling

DTechnical
Information**E**

Index

Threading tool holder (internal)

ZSIR/L



Article	✱	Stock	Dimensions [mm]								Inserts
			ød	b	L	h	s	L ₁	D _{min}		
ZSIR0016K11C	✱	○	16	15.5	125	15	10	20.9	12	Z11IR**	
ZSIR0016M11C	✱	○	16	16	150	15	10.5	25.9	16	Z11IR**	
ZSIR0016M16C	✱	○	16	15.5	150	15	12	27	20	Z16IR**	
ZSIR0020M16C	✱	○	20	19	150	18	14	28.7	25	Z16IR**	
ZSIR0020Q16C	✱	○	20	19	180	18	14	34	25	Z16IR**	
ZSIR0025M16C	✱	○	25	24	150	23	17	28.8	32	Z16IR**	
ZSIR0032R16C	✱	○	32	31	200	30	22	30.9	40	Z16IR**	
ZSIR0032S16C	✱	○	32	31	250	30	22	30.9	40	Z16IR**	
ZSIR0040T16C	✱	○	40	38.5	300	37	27	31.5	50	Z16IR**	
ZSIR0020Q22C	✱	○	20	19	180	18	15	35	25	Z22IR**	
ZSIR0025R22C	✱	○	25	24	200	23	19	39	32	Z22IR**	
ZSIR0032S22C	✱	○	32	31	250	30	22	36.4	40	Z22IR**	
ZSIR0040T22C	✱	○	40	38.5	300	37	27	37.2	50	Z22IR**	


● Ex stock ○ On demand

* With internal cooling

Spare parts						
	Insert	Z11IR**	Z16IR**	Z16IR**	Z22IR**	Z22IR**
	ød	16	16	20-50	20	25-50
	Screw	I60M2,5×6,5T (1,0 Nm)			I60M5×13,2 (6,7 Nm)	I60M4×15X (3,4 Nm)
	Screw		I60M3,5×08TT (2,7 Nm)	I60M3,5×12TT (2,7 Nm)		
	Screw (shim)			SM4×8C (2,6 Nm)		SM5×8,5C (4,0 Nm)
	Shim			MT16-__MN		MT22-__MN
	Wrench (screw)	WT08IP	WT10IP	WT10IP	WT15IP	WT15IP

Threading tool holder (internal)

ZSIR/L




Article	*	Stock	Dimensions [mm]							Inserts
			ød	b	L	h	s	L ₁	D _{min}	
ZSIL0016K11C	*	○	16	15.5	125	15	10	20.9	12	Z11IL**
ZSIL0016M11C	*	○	16	16	150	15	10.5	25.9	16	Z11IL**
ZSIL0016M16C	*	○	16	15.5	150	15	12	27	20	Z16IL**
ZSIL0020M16C	*	○	20	19	150	18	14	28.7	25	Z16IL**
ZSIL0020Q16C	*	○	20	19	180	18	14	34	25	Z16IL**
ZSIL0025M16C	*	○	25	24	150	23	17	28.8	32	Z16IL**
ZSIL0032R16C	*	○	32	31	200	30	22	30.9	40	Z16IL**
ZSIL0032S16C	*	○	32	31	250	30	22	30.9	40	Z16IL**
ZSIL0040T16C	*	○	40	38.5	300	37	27	31.5	50	Z16IL**
ZSIL0020Q22C	*	○	20	19	180	18	15	35	25	Z22IL**
ZSIL0025R22C	*	○	25	24	200	23	19	39	32	Z22IL**
ZSIL0032S22C	*	○	32	31	250	30	22	36.4	40	Z22IL**
ZSIL0040T22C	*	○	40	38.5	300	37	27	37.2	50	Z22IL**

● Ex stock ○ On demand

* With internal cooling

Spare parts						
	Insert ød	Z11IR** 16	Z16IR** 16	Z16IR** 20-50	Z22IR** 20	Z22IR** 25-50
	Screw	I60M2,5×6,5T (1,0 Nm)			I60M5×13,2 (6,7 Nm)	I60M4×15X (3,4 Nm)
	Screw		I60M3,5×08TT (2,7 Nm)	I60M3,5×12TT (2,7 Nm)		
	Screw (shim)			SM4×8C (2,6 Nm)		SM5×8,5C (4,0 Nm)
	Shim			MT16-__MN		MT22-__MN
	Wrench (screw)	WT08IP	WT10IP	WT10IP	WT15IP	WT15IP



FD flat drill

Solid carbide drills

System code – solid carbide drills
FD flat drills

C36–C37
C38–C40

C

A

Turning

B

Milling

C

Drilling

D

Technical
Information

E

Index

A

1 5 3 6 SU 05 (C) – 0850 (S)

1

2

3

4

5

6

7

8

9

Turning

Type	
Code	Description
1	Forets

1

Shank type	
Code	Description
1	Straight shank
2	Square shank DIN 10
3	Double flattened straight shank DIN 1809
5	Straight shank DIN 6535 HA
6	Weldon shank DIN 6535 HB
7	Whistle Notch shank DIN 6535 HE
9	Morse taper shank

2

B

Milling

Drill type	
Code	Description
0	Twist drill
3	Universal twist drill
4	NC tapping device
5	Step drill
6	Three-lips drill
7	Straight flute drill
8	Deep hole drill

3

Tool length	
Code	Description
1	DIN 338
2	DIN 1897
3	QJ/ZZQ(TO)01.001.002
4	DIN 6537 K
5	DIN 6539
6	DIN 6537 L
7	Factory standard ZCC-C
8	Factory standard ZCC-D
9	Factory standard ZCC-E

4

C

Drilling

Application	
Code	Description
FD	Flat drills with 180° for any application
UD	Twist drills for tough materials
GD	Twist drills for high feeds
SU	Twist drill for general machining
SUK	Twist drill for cast iron
SL	Twist drill for deep hole drilling
SLK	Deep hole drill for cast iron
SP	Pilot drill
SH	Twist drill for hardened materials
SC	Twist drill for non-ferrous metals and cast iron
PA	Three-lips drill for non-ferrous metals and cast iron
PC	Straight flute drill for non-ferrous metals and cast iron

5

D

Technical
Information

E

Index

L/D relation		Angle	
Drill		NC tapping device	
Code	Description	Code	Description
03	3xD	90	90°
05	5xD	120	120°
08	8xD		
10	10xD		
12	12xD		
15	15xD		
20	20xD		
30	30xD		

6

With inner cooling

7

Bore diameter [mm]	
Code	Description
0200	2,0
0850	8,5
1800	18,0
...	

8

Shank diameter [mm]	
Code	Description
S	4,0

9
A

Turning

B

Milling

C

Drilling

D

Technical
Information

E

Index



a Boring



b Drilling



c Profile drilling




d Centering

FD flat drills

180° solid carbide drills for any application

YOUR BENEFITS

- Particularly well suited for creating spot faces efficiently
- Possible to drill holes in inclined surfaces up to 55° with no pre-milling
- **Reduced burr formation** in drilling applications involved thin components
- **Universal tool** for all materials



Feed calculator

ISO group	Material	Cutting speed v_c (m/min)	Feed factor F_m
P	Low-alloy steel	80	0,015
P	High-alloy steel	60	0,012
K	Cast iron	80	0,015
K	Cast steel	60	0,015
M	Stainless steel	45	0,01
N	Aluminium	120	0,02

Formula: feed per revolution (F_n) $D \times F_m$

Example: drill diameter (D) 10 mm
material aluminium

$$F_n = 10 \text{ mm} \times 0,02 = 0,2 \text{ mm/r}$$

Reduce the feed rate by the following factor with inclined holes:

Angle	Feed rate multiplier
5°–30°	0,75
35°–50°	0,50

Formula: feed per revolution (F_n) $D \times F_m \times \text{multiplier}$

Example: drill diameter (D) 10 mm
material aluminium
drilling angle 30°

$$F_n = 10 \text{ mm} \times 0,02 \times 0,75 = 0,15 \text{ mm/r}$$

Your notes

.....

.....

.....

.....

.....

.....

.....

.....

.....

.....

FD drill 3xD


General machining



- Type of shank DIN 6535HA
- Coolant exit, axial concentric



Internal coolant



Article	*	Dimensions [mm]						Grade
		d ₁ (m7)	d ₂ (h6)	l ₁	l ₂	l ₃	l ₄	KDG305
1534FD03C-0300	*	3	6	62	20	14	36	●
1534FD03C-0350	*	3.5	6	62	20	14	36	○
1534FD03C-0400	*	4	6	66	24	17	36	●
1534FD03C-0450	*	4.5	6	66	24	17	36	○
1534FD03C-0500	*	5	6	66	28	20	36	●
1534FD03C-0550	*	5.5	6	66	28	20	36	○
1534FD03C-0600	*	6	6	66	28	20	36	●
1534FD03C-0650	*	6.5	8	79	34	24	36	●
1534FD03C-0700	*	7	8	79	34	24	36	●
1534FD03C-0750	*	7.5	8	79	41	29	36	○
1534FD03C-0800	*	8	8	79	41	29	36	●
1534FD03C-0850	*	8.5	10	89	47	35	40	○
1534FD03C-0900	*	9	10	89	47	35	40	●
1534FD03C-0950	*	9.5	10	89	47	35	40	○
1534FD03C-1000	*	10	10	89	47	35	40	●
1534FD03C-1050	*	10.5	12	102	55	40	45	○
1534FD03C-1100	*	11	12	102	55	40	45	●
1534FD03C-1150	*	11.5	12	102	55	40	45	○
1534FD03C-1200	*	12	12	102	55	40	45	●
1534FD03C-1250	*	12.5	14	107	60	43	45	○
1534FD03C-1300	*	13	14	107	60	43	45	●
1534FD03C-1350	*	13.5	14	107	60	43	45	○
1534FD03C-1400	*	14	14	107	60	43	45	●
1534FD03C-1450	*	14.5	16	115	65	45	48	○
1534FD03C-1500	*	15	16	115	65	45	48	●
1534FD03C-1550	*	15.5	16	115	65	45	48	○
1534FD03C-1600	*	16	16	115	65	45	48	●
1534FD03C-1650	*	16.5	18	123	73	51	48	○
1534FD03C-1700	*	17	18	123	73	51	48	●
1534FD03C-1750	*	17.5	18	123	73	51	48	○
1534FD03C-1800	*	18	18	123	73	51	48	●
1534FD03C-1850	*	18.5	20	131	79	55	50	○
1534FD03C-1900	*	19	20	131	79	55	50	●
1534FD03C-1950	*	19.5	20	131	79	55	50	○
1534FD03C-2000	*	20	20	131	79	55	50	●

● Ex stock ○ On demand

* With internal cooling

Application field


P	M	K	N	S	H
✓	✓	✓	✓		

✓ Very suitable

✓ Suitable

The easy way to order your custom-made special tool


Are there specific applications at your company where having custom tools tailored to your unique needs would deliver real benefits both in terms of logistics and at a technical and commercial level? ZCC Cutting Tools is there to advise and assist you during the planning, development and ordering process. Use our new online tool to request a special tool and get your personal quotation in just a few short steps (www.zccct-europe.com).



'Online tool for special tools' launch page where you can select the tool category

Selecting the tool category

Scan the QR code on this page to go directly to the launch page of our online tool where you can request the special tool you need. You can begin by selecting the tool category you need. It's that easy.



Define the relevant tool parameters

Defining the tool parameters

You are now guided step by step through the process. You can also securely upload your drawings, diagrams and 3D models (where available).

The fast and direct way to order your special tool from ZCC Cutting Tools Europe.



Now go directly to the new **special tool form** on our website and get started.



Celebrating 20 years of growth built on partnership

2023 marks a special year in the success story that is ZCC Cutting Tools Europe GmbH. It all started 20 years ago in Düsseldorf when we began offering cutting tools targeted at the European market. While our business was small to begin with, we steadily expanded, with a constant focus on growth and on our customers.

A strong brand promise

From day one, ZCC Cutting Tools Europe has shown a constant commitment to offering **premium technological products** that are tailored to the requirements of the individual target groups, **represent a strong value proposition** and improve quality, productivity and efficiency in the production environments of our customers from across a range of industrial segments. We also provide an array of **associated services** that deliver the quality our customers on the European market demand.

Technological expertise and resources

ZCC Cutting Tools has the **expertise, capabilities and resources** required across the entire value chain in the development and production of cutting tools. This is our USP that has allowed us to offer and continue to offer these products and services. From the start, we have passed on this added value to our customers and business partners who have benefited from this ever since.

Trust built on 20 years of continuity

We now **develop and test** products and solutions in Europe for the markets **in Europe** in close consultation with our customers. We offer a **full range of standard products** and **customised special solutions**. Our logistics processes guarantee **on-time delivery** in all markets across Europe.

We present our latest new products to kick off our 20th year anniversary, and look forward to growing our partnership with you.



Go to PDF online

European Headquarters

ZCC Cutting Tools Europe GmbH

www.zccct-europe.com

Wanheimer Str. 57, 40472 Düsseldorf, Germany

Tel.: +49 (0)211-989240-0

Fax: +49 (0)211-989240-111

E-mail: info@zccct-europe.com

Branch Office France

ZCC Cutting Tools Europe GmbH

Succursale Française

www.zccct-europe.com

14, Allée Charles Pathé, 18000 Bourges, France

Tel.: +33 (0)2 45 41 01 40

Fax: +33 (0)800 74 27 27

E-mail: ventes@zccct-europe.com

Branch Office UK

ZCC Cutting Tools Europe GmbH

UK Division

www.zccct-europe.com

4200 Waterside Centre, Solihull Parkway,
Birmingham Business Park.

Birmingham, West Midlands, B37 7YN, UK

Tel.: +44 (0)121-809 5469

Fax: +49 (0)211-989240-111

E-mail: infouk@zccct-europe.com



**ZCC Cutting Tools
Europe GmbH**

© Copyright by ZCC Cutting Tools Europe GmbH